

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An interface method for a logical circuit comprising a logical operation element, comprising:

defining a hardware interface, using a first interface definition language which is partly common to a second interface definition language directed to a software object, wherein the first interface definition language has means for defining a plurality of functions, each function having a function name, and a function return value, and at least one function having at least one function argument, such that the software object can realize the hardware interface by using only the second interface definition language;

providing at least means for inputting for identifying the function name defined by the first interface definition language for a server interface circuit in order to realize the interface among the means for inputting for identifying the function name defined by the first interface definition language, means for inputting and outputting the argument, and means for outputting the return value;

determining whether the function is the at least one function having the at least one function argument; and

performing at least one of inputting the function argument, outputting the function argument and outputting the function return value.

2. (Currently Amended) An interface method for a logical circuit comprising a logical operation element, comprising:

defining a hardware interface, using a first interface definition language which is partly common to a second interface definition language directed to a software object, wherein the first interface definition language has means for defining a plurality of functions,

each function having a function name and a function return value, and at least one function having at least one function argument, such that the software object can realize the hardware interface by using only the second interface definition language; and

providing at least means for outputting for identifying the function name defined by the first interface definition language for a client interface circuit in order to realize the interface among the means for outputting for identifying the function name defined by the first interface definition language, means for inputting and outputting the argument, and means for inputting the return value;

determining whether the function is the at least one function having the at least one function argument; and

performing at least one of inputting the function argument, outputting the function argument and outputting the function return value.

3. (Currently Amended) An interface method for a logical circuit comprising a logical operation element, comprising:

defining a hardware interface, using a first interface definition language which is partly common to a second interface definition language directed to a software object, wherein the first interface definition language has means for defining a plurality of functions, each function having a function name and a function return value, and at least one function having at least one function argument, such that the software object can realize the hardware interface by using only the second interface definition language, wherein the logical circuit comprises:

a server logical circuit, as a server interface circuit for realizing the interface, having at least means for inputting for identifying the function name defined by the first interface definition language among the means for inputting for identifying the function

name defined by the first interface definition language, means for inputting and outputting the argument, and means for outputting the return value, and

a client logical circuit, as a client interface circuit for realizing the interface, having at least means for outputting for identifying the function name defined by the first interface definition language among the means for outputting for identifying the function name defined by the first interface definition language, means for inputting and outputting the argument, and means for inputting the return value, and

data being transferred from the means for outputting for identifying the function name of the client logical circuit to the means for inputting for identifying the function name of the server logical circuit,

the server logical circuit and the client logical circuit each having at least one of the means for outputting the return value and the means for inputting the return value, and data can be transferred from the means for outputting the return value to the means for inputting a return value;

determining whether the function is the at least one function having the at least one function argument; and

performing at least one of inputting the function argument, outputting the function argument and outputting the function return value.

4. (Currently Amended) A device having a hardware interface and a logical circuit comprising a logical operation element, which defines an interface, using a first interface definition language which is partly common to a second interface definition language directed to a software object, wherein the first interface definition language has means for defining a plurality of functions, each function having a function name and a return value, and at least one function having at least one function argument,

wherein the software object can realize the hardware interface by using only the second interface definition language and a server interface circuit for realizing the interface comprises means for inputting for identifying the function name defined by the first interface definition language among the means for inputting for identifying the function name defined by the first interface definition language, means for inputting and outputting the argument, and means for outputting the return value, means for determining whether the function is the at least one function having the at least one function argument, and means for performing at least one of inputting the at least one function argument and outputting the at least one function argument.

5. (Currently Amended) A device having a hardware interface and a logical circuit, which defines an interface, using a first interface definition language which is partly common to a second interface definition language directed to a software object and has means for defining a plurality of functions, each function having a function name and a function return value and at least one function having at least one function argument, comprising:

a client interface circuit for realizing the interface comprises means for outputting for identifying the function name defined by the first interface definition language among the means for outputting for identifying the function name defined by the first interface definition language, means for inputting and outputting the argument, and means for inputting the return value;

an argument number detection section for determining whether the function is the at least one function having the at least one function argument; and

an argument register for inputting the at least one function argument and for outputting the at least one function argument, wherein the software object can realize the hardware interface by using only the second interface definition language.

6. (Previously Presented) The device according to claim 5, wherein

the client interface circuit has a connection terminal and a register,
the connection terminal of the client interface is connected to the server
interface circuit or a system bus, and

when the connection terminal of the client interface is connected to the server
interface circuit, the device connected with the server interface circuit is drivable via the
server interface circuit, and

when the connection terminal of the client interface is connected to the system
bus, a value of the register within the client interface can be read via a central processing
device such that the central processing device can serve in the place of the device connected
with the server interface circuit.

7. (Canceled)

8. (Previously Presented) An interface method according to claim 3, further
comprising:

the server logical circuit and the client logical circuit each having the means
for inputting and outputting the argument and data being transferred between the means for
inputting and outputting the argument of the server logical circuit and means for inputting and
outputting the argument of the client logical circuit.

9. (Currently Amended) An interface method for a logical circuit comprising a
logical operation element, comprising:

defining a hardware interface, using an interface definition language having
means for at least defining a plurality of functions, each function having a function name and
a function return value, and at least one function having at least one function argument;

providing at least means for outputting for identifying the function name
defined by the interface definition language for a client interface circuit in order to realize the
interface among the means for outputting for identifying the function name defined by the

interface definition language, means for inputting and outputting the argument, and means for inputting the return value, wherein the client interface circuit realizes the interface by using another interface definition language;

determining whether the function is the at least one function having the at least one function argument; and

performing at least one of inputting the function argument, outputting the function argument and outputting the function return value.

10. (Currently Amended) An interface method for a logical circuit comprising a logical operation element, comprising:

defining a hardware interface, using an interface definition language having means for defining a plurality of functions, each function having a function name and a return value, and at least one function having at least one argument, wherein the logical circuit comprises:

a server logical circuit, as a server interface circuit for realizing the interface, having at least means for inputting for identifying the function name defined by the interface definition language among the means for inputting for identifying the function name defined by the interface definition language, means for inputting and outputting the argument, and means for outputting the return value, and

a client logical circuit, as a client interface circuit for realizing the interface, having at least means for outputting for identifying the function name defined by the interface definition language among the means for outputting for identifying the function name defined by the interface definition language, means for inputting and outputting the argument, and means for inputting the return value, wherein the client interface circuit realizes the interface by using another interface definition language. and

data being transferred from the means for outputting for identifying the function name of the client logical circuit to the means for inputting for identifying the function name of the server logical circuit,

the server logical circuit and the client logical circuit each having at least one of the means for outputting the return value and the means for inputting the return value, and data can be transferred from the means for outputting the return value to the means for inputting a return value;

determining whether or not the function has the at least one function argument; and

performing at least one of inputting the function argument, outputting the function argument and outputting the function return value.

11. (Currently Amended) A device having a hardware interface and a logical circuit comprising a logical operation element, which defines an interface, using an interface definition language having means for defining a function name, an argument, and a return value for each function defined by the function name, wherein

a server interface circuit for realizing the interface ~~comprises~~ comprises:
_____ means for inputting for identifying the function name defined by the interface definition language among the means for inputting for identifying the function name defined by the interface definition language, means for inputting and outputting the argument, and means for outputting the return value;

_____ an argument number detection section for determining whether the function is the at least one function having the at least one function argument; and

_____ an argument register for inputting the at least one function argument and outputting the at least one function argument, and wherein

a client interface circuit realizes the interface by using another interface definition language.

12. (Currently Amended) A device having a hardware interface and a logical circuit, which defines an interface, using an interface definition language having means for defining a plurality of functions, each function having a function name and a function return value, and at least one function having at least one function argument,

wherein a client interface circuit for realizing the interface realizes the interface by using another interface definition language and comprises means for outputting for identifying the function name defined by the interface definition language among the means for outputting for identifying the function name defined by the interface definition language, means for inputting and outputting the argument, and means for inputting the return value, means for determining whether the function is the at least one function having the at least one function argument, and means for performing at least one of inputting the at least one function argument and outputting the at least one function argument.

13. (Previously Presented) The device according to claim 12, wherein
the client interface circuit has a connection terminal and a register,
the connection terminal of the client interface is connected to the server interface circuit or a system bus, and

when the connection terminal of the client interface is connected to the server interface circuit, the device connected with the server interface circuit is drivable via the server interface circuit, and

when the connection terminal of the client interface is connected to the system bus, a value of the register within the client interface can be read via a central processing device such that the central processing device can serve in the place of the device connected with the server interface circuit.

14. (Previously Presented) An interface method according to claim 10, further comprising:

the server logical circuit and the client logical circuit each having the means for inputting and outputting the argument and data being transferred between the means for inputting and outputting the argument of the server logical circuit and means for inputting and outputting the argument of the client logical circuit.